



# Kata™ EX2-M

Dual motion monitor arm

# KataEX2-M

## Dual motion monitor arm



tension adjustment



integrated tool storage



grommet mount



desk clamp



connection sleeve

### Product specs

- Finger touch dynamic height adjustment
- Recommended for worksurfaces 30.0" deep or less
- 15.01" arm extension
- 3.39" arm retraction
- +90°/-45° monitor tilt
- ±90° VESA rotation
- 4.0 lb.–20.0 lb. weight capacity (*per arm*)
- 15.99" pole height (*includes base*)
- VESA 75mm/100mm quick release
- 180° lock-out feature
- Specify a grommet mount or a desk clamp mount
- Tension adjustment indicator for precision installation
- Each connection sleeve can accommodate up to three monitors depending on the configuration
- Partially assembled for quick installation
- Integrated cord management
- Integrated tool holder
- Meets or exceeds ANSI/BIFMA x5.5 guidelines
- 32.72" max. monitor width  
*Bezel measured left to right.*  
*Max. width is contingent on weight capacity.*
- Designed for ESI by Roger Webb Associates of London
- Warranty: 15 yr.

### Model #

- ☐ KATAEX2-DC-M-SLV
- ☒ KATAEX2-DC-M-BLK
- ☐ KATAEX2-DC-M-WHT
- ☐ KATAEX2-GM-M-SLV
- ☒ KATAEX2-GM-M-BLK
- ☐ KATAEX2-GM-M-WHT

### KataEX monitor arm key

- F - Fixed monitor arm
- M - Motion monitor arm
- S - Slider mount

### Available mounting options

- DC - Desk clamp
- GM - Grommet mount

### KataEX for every need

- As workstation needs change, so can the KataEX configurations. Additional components sold separately
- Benching system mount(s) available

Call our Customer Service Department for compatibility and pricing for custom configurations.

# KataEX2-M

Dual motion monitor arm

