



### GOOD

#### Triumph-LX™

- 220 lbs. base lifting capacity
- 1.4"/sec. adjustment speed
- 17.0" height adjustment range
- 26.5"–43.5" (low/high) *(excluding worksurface)*
- Two-stage adjustable table base
- Adjustable width frame accommodates worksurfaces 36.0"–72.0"
- Two motors
- Digital keypad with three memory settings
- Soft start and stop
- Anti-collision safety feature
- Locking casters are available
- Low standby power consumption
- Exceeds BIFMA x5.5 guidelines

### BETTER

#### Victory-LX™ 2 & 3-leg

- 220 lbs. (2-leg) | 330 lbs. (3-leg) base lifting capacity
- 1.4"/sec adjustment speed
- 26.0" height adjustment range
- 21.5"–47.5" (low/high) *(excluding worksurface)*
- Three stage adjustable legs
- Adjustable width frame accommodates worksurfaces 36.0"–72.0" (2-leg) and 48.0"–84.0" (3-leg)
- Soft start and stop
- Frame and column connect and lock for quick and easy assembly
- Digital keypad with three memory settings
- Anti-collision safety feature
- Locking casters available
- Two motors (2-leg) | Three motors (3-leg)
- Meets or exceeds BIFMA x5.5, G1, and CSA CAN/CGSB44.227 guidelines
- Works with peds or storage with 20.0" max. height
- Low standby power consumption
- 3-leg can be configured for 90° or 120° with a universal bracket

### BEST

#### All-Flex® 2 & 3-leg

- 265 lbs. (2-leg) | 330 lbs. (3-leg) base lifting capacity
- 1.5"/sec adjustment speed
- One part number for all 2-leg sizes
- 26.0" height adjustment range
- 23.3"–49.3" (low/high) *(excluding worksurface)*
- Three-stage adjustable legs
- Provides adjustable cross channels, top support, and feet making it one of the most adjustable table bases on the market.
- Foot is adjustable to 22.0" or 28.0" *(patented design)*
- Adjustable width frame to fit worksurfaces 36.0"–84.0" wide
- Adjustable width frame accommodates worksurfaces 36.0"–72.0" (2-leg) and 48.0"–84.0" (3-leg)
- Digital keypad with four memory settings
- Anti-collision safety feature
- Soft start and stop
- Leg columns fold out for easy assembly
- Low standby power consumption
- Two motors (2-leg) | Three motors (3-leg)
- Locking casters are available
- 3-leg can be configured for 90° or 120° with a universal bracket

MODEL # LIST PRICE  
   2T-LX-\_\_\_ \$943

MODEL # LIST PRICE  
   2VT-LX-\_\_\_ \$1,113  
   3VT-LX-\_\_\_ \$1,610

MODEL # LIST PRICE  
   FLEX2-\_\_\_ \$1,645  
   FLEX3-\_\_\_ \$2,486



GOOD	BETTER	BEST
	<b>Q Crank</b>	<b>Weight Adjustable Espree</b>
	<ul style="list-style-type: none"> <li>• Crank height adjustment</li> <li>• 220 lb. base lifting capacity</li> <li>• 1.0" per two cranks adjustment speed</li> <li>• 17.5" height adjustment range 24.8"–42.3" (low/high) <i>(excluding worksurface)</i></li> <li>• Two stage adjustable legs</li> <li>• Adjustable width frame accommodates worksurfaces 36.0"–72.0"</li> <li>• Locking casters available</li> </ul>	<ul style="list-style-type: none"> <li>• Pneumatic height adjustment</li> <li>• 44 lbs.–143 lbs. base lifting capacity (2ESP-WA-C48)</li> <li>• 52 lbs.–163 lbs. base lifting capacity (2ESP-WA-C60)</li> <li>• 20.0" height adjustment range 26.0"–46.0" (low/high) <i>(excluding worksurface)</i></li> <li>• Two stage adjustable legs</li> <li>• Foot is adjustable to 22.0" or 28.0" <i>(patented design)</i></li> <li>• Fixed width frame</li> <li>• Weight adjustable with adjustment gauge</li> <li>• Locking casters available</li> </ul>

MODEL #	LIST PRICE
<input type="radio"/> <input checked="" type="radio"/> QCRANK-24S-___	\$922
<input type="radio"/> <input checked="" type="radio"/> QCRANK-24L-___	\$922
<input type="radio"/> <input checked="" type="radio"/> QCRANK-30S-___	\$922
<input type="radio"/> <input checked="" type="radio"/> QCRANK-30L-___	\$922

MODEL #	LIST PRICE
<input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> 2ESP-WA-C48-___	\$2,107
<input type="radio"/> <input checked="" type="radio"/> <input type="radio"/> 2ESP-WA-C60-___	\$2,188