

Kata[™]EX6-FF

Six fixed + fixed monitor arm

KataEX6-FF

Six fixed + fixed monitor arm



tension adjustment



integrated tool storage



grommet mount



desk clamp



connection sleeve



Product specs

- Manual height adjustment
- · Recommended for worksurfaces 30.0" deep or less
- · 24.77" outside arm extension
- · 8.52" center arm extension
- 5.12" arm retraction
- +90°/-45° monitor tilt
- ±90° VESA rotation
- Up to 20.0 lb. weight capacity (per arm)
- 25.99" pole height (includes base)
- · VESA 75mm/100mm quick release
- · 180° lock-out feature
- · Desk clamp mount only
- Tension adjustment indicator for precision installation
- Each connection sleeve can accommodate up to three monitors depending on the configuration
- · Partially assembled for quick installation
- · Integrated cord management
- · Integrated tool holder
- Meets or exceeds ANSI/BIFMA x5.5 guidelines
- 26.14" max. monitor width
 Bezel measured left to right.
 Max. width is contingent on weight capacity.
 Note: monitor height/weight might limit size
- Designed for ESI by Roger Webb Associates of London
- · Warranty: 15 yr.

Model

KATAEX6-DC-FF-SLV

KATAEX6-DC-FF-BLK

○ KATAEX6-DC-FF-WHT

KataEX monitor arm key

Available mounting options

F - Fixed monitor arm

DC - Desk clamp

M - Motion monitor arm

GM - Grommet mount

S - Slider mount

KataEX for every need

- As workstation needs change, so can the KataEX configurations. Additional components sold separately
- · Benching system mount(s) available

Call our Customer Service Department for compatibility and pricing for custom configurations.



KataEX6-FF

