esi.



250 lbs. base lifting capacity 1.4"/sec adjustment speed 26.1" height adjustment range

- 21.6"-47.7" (low/high) (excluding worksurface)

Frame and column connect and lock for quick and easy assembly

Gyro sensor anti-collision

Three stage adjustable legs

Adjustable width frame

Table base is UL962 listed

Meets or Exceeds BIFMA x5.5 requirements

Meets BIFMA GI-2013 ergonomic standards when used with a 1.0" worksurface

Complete tables available (base and top)



360 lb. base lifting capacity 1.4"/sec adjustment speed 26.1" height adjustment range

- 21.5"-47.5" (low/high) (excluding worksurface)

Frame and column connect and lock for quick and easy assembly

Gyro sensor anti-collision

Three stage adjustable legs

Adjustable width frame

Table base is UL962 listed

Meets or exceeds BIFMA x5.5, GI and CSA CAN/CGSB44.227

Complete tables available (base and top)











The VictoryLX Series is an ideal solution for a wide range of space planning needs. With adjustable cross channels and 26.0" of height adjustment, this table base accommodates a wide range of users and various size worksurfaces. The connect and lock frame and column make for a quick and easy assembly. Designed to offer endless possibilities, freedom, and flexibility in configuring workspace layouts.

